

FTP, Category 5, LSOH

P/N: KEL-C5E-F-005	length 0.5 m	P/N: KEL-C5E-F-050	length 5 m
P/N: KEL-C5E-F-010	length 1 m	P/N: KEL-C5E-F-070	length 7 m
P/N: KEL-C5E-F-015	length 1.5 m	P/N: KEL-C5E-F-100	length 10 m
P/N: KEL-C5E-F-020	length 2 m	P/N: KEL-C5E-F-150	length 15 m
P/N: KEL-C5E-F-030	length 3 m	P/N: KEL-C5E-F-xxx	other



features

- cable shielded with AL/PET foil, stranded wires, halogen-free sheath
- connector RJ45 is compliant with IEC 60603-7 standard by its dimensions and transmission features
- enables transmission of all high-speed protocols up to 1000BASE-T
- guarantees a bandwidth of 100 MHz
- shielded against electromagnetic interference
- complies with the requirements for fire prevention arrangements in buildings with higher concentration of people

application

- primary (Campus), secondary (Riser), tertiary (Horizontal)
- IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T
- IEEE 802.5 16 MB; ISDN; FDDI; ATM

construction

Conductor	stranded bare copper wire, AWG 26 / 7	
Sheath	low smoke, halogen-free (LSOH)	
Contact pin material	phosphor-bronze alloy coated with 50 µ of gold	
Boots material	polycarbonate	
Outer cable diameter	5,4 mm	
Color (standard)	cable	gray RAL7035
	boots	gray RAL7035

mechanical properties

Insertion / extraction cycles	min. 750	
Temperature range	operation	-25 °C to +60 °C
	installation	-25 °C to +60 °C
Min. bending radius	25 mm	

electrical properties at 20°C

Voltage rating	-	125 V AC
Current rating	-	1 A
Contact resistance	100 mA (DC or 1000Hz)	50 mΩ max.
Insulation resistance	100 V DC	100 MΩ min.

related products

P/N: KEJ-C5E-S-TL	Keystone Jack, Category 5E, RJ45/s
P/N: 601140-AP + KEJ-C5E-S-TL(2)	Modulo50 outlet, Category 6, 2xRJ45/s
P/N: 601120-UP + KEJ-C5E-S-TL(2)	Modulo45 outlet, Category 6, 2xRJ45/s
P/N: KEP-C5E-S-1TL	Patch panel, Category 5E, 24xRJ45/s
P/N: KE300S24LSOH	STP cable 4x2xAWG24, Category 5E, 125 MHz, LSOH